

Pedrali SpA

SP 122 - 24050 Mornico al Serio - Bergamo - Italia

Ufficio Commerciale Italia +39 035 8358810

Export Dept. +39 035 8358840


Fax +39 035 8358888



www.pedrali.it - info@pedrali.it



LOTUS 4415F_AC + S_TX

design Pedrali R&D



4 Pz = 5 
MC 0,149
1 Pz = 2 
MC 0,091

Smontata
Unassembled KD



Kg

<p>MATERIALI Materials / Materialien / Matériaux / Materiales</p>	<p>- SEDUTA / SEAT / SITZ / ASSISE / ASIENTO Struttura in legno, imbottita con poliuretano espanso flessibile, densità 40/50 kg/m³, rivestita / Wood frame, internal seat made of flexible expanding polyurethane (40/50 kg/m³ density), upholstered / Struktur aus Holz, gepolstert mit Polyurethan flexibel (40/50 kg/m³ dicht), bezogen / Structure en bois, rembourrée en polyuréthane expansé souple (densité 40/50 kg / m³), garnie / Estructura de madera, tapizada en espuma de poliuretano flexible (densidad 40/50 kg / m³)</p> <p>- TESSUTO / FABRIC / STOFF / TISSU / TEJIDO Cat. A - C - G - H - P</p> <p>- COLONNA / COLUMN / SÄULE / COLONNE / COLUMNA Tubo Ø50 mm, acciaio Inox AISI 304 / Tube Ø50 mm, stainless steel AISI 304 / Rohr Ø50 mm, Edelstahl AISI 304 / Tube Ø50 mm, acier Inox AISI 304 / Tubo Ø50 mm, acero inoxidable AISI 304</p> <p>- POGGIAPIEDI / FOOTREST / FUßRASTE / REPOSE-PIEDS / REPOSA PIES Ø350 mm, quattro razze, in acciaio inox / Ø350 mm, four spokes, stainless steel / Ø350 mm, vier Speichen aus Edelstahl / Ø350 mm, quatre rayons, en acier inoxydable / Ø350 mm, cuatro radios de acero inoxidable</p> <p>- BASE / BASE / BODENPLATTE / BASE / BASE Ø400 mm, ghisa, sabbiata, verniciata con polvere epossipoliestere / Ø400 mm, cast iron, sandblasted, epoxy-polyester powder coating / Ø400 mm, Gusseisen, Sandgestrahlt, epoxy-polyester pulverbeschichtet / Ø400 mm, fonte, sablée, vernissage à poudre époxy-polystère / Ø400 mm, hierro fundido, arenada, pintada epoxidica</p> <p>- CROCIERA / CROSS / KREUZ / CROIX / CRUCETA Mod. 4006 230x230 mm, ghisa, sabbiata, verniciata con polvere epossipoliestere / 230x230 mm, cast iron, sandblasted, epoxy-polyester powder coating / 230x230 mm, Gusseisen, Sandgestrahlt, epoxy-polyester pulverbeschichtet / 230x230 mm, fonte, sablée, vernissage à poudre époxy-polystère / 230x230 mm, hierro fundido, arenada, pintada epoxidica</p> <p>- COPRIBASE / COVER-BASE / ABDECKUNG / COUVRE-SOCLE / CUBRE BASE Acciaio Inox AISI 304 / Stainless steel AISI 304 / Edelstahl AISI 304 / Acier inox AISI 304 / Acero inoxidable AISI 304</p> <p>- FINITURA POGGIAPIEDI / FOOTREST FINISH / AUSFÜHRUNG FUSSRASTE / FINITIONS REPOSE-PIEDS / ACABADO REPOSA PIES ST - Satinato / Satinized / Satiniert / Satiné / Satinado</p> <p>- FINITURA TUBO E COPRIBASE / TUBE AND COVER-BASE FINISH / AUSFÜHRUNG VON GESTELL UND ABDECKUNG / FINITIONS TUBE ET COUVRE-SOCLE / ACABADO TUBO Y CUBRE BASE Satinati Scotch-Brite™ / Scotch-brite™ brushed / Gebürstet / Satinés scotch-brite™ / Satinados Scotch-Brite™</p>
<p>UTILIZZO Uso / Verwendung / Emploi / Uso</p>	<p>Contract, indoor</p>
<p>NORMATIVE e CERTIFICAZIONI Regulations and certificates / Bestimmungen und Zertifikat / Normatives et certifications / Normativas y certificados</p>	<p>Conforme alla norma: resistenza a fatica appoggiapiedi, 100.000 cicli EN 1728:2012 - EN 16139:2013, livello L2 - estremo Conforming to: foot rest durability test, 100.000 cycles EN 1728:2012 - EN 16139:2013, level L2 - extreme</p>
<p>ACCESSORI Accessories / Zubehörteile / Accessoires / Accesorios</p>	<p>cod. KIT/FELTRO.CURVO.6 Kit n° 6 feltrini adesivi per basi tonde / kit n°6 adhesive felts for round bases / Kit n° 6 Filzgleiter für runden sockel / Kit n° 6 feutres adhesifs pour bases rondes / Kit n° 6 topos de fieltro para bases redondas</p>